



10HDR-AW

Crossover Frequencies	Filter	Slope	Frequency(Hz)
Recommended	High Pass	12db/octButwrth	35
	Low Pass	24db/octButwrth	80-160
Limiter	Voltage		
RMS	52		
PEAK 3dB above	69		

12HDR-AW

Crossover Frequencies	Filter	Slope	Frequency(Hz)
Recommended	High Pass	12db/octButwrth	30
	Low Pass	24db/octButwrth	80-120
Limiter	Voltage		
RMS	89		
PEAK 3dB above	126		

112HD / 212HD

Crossover Frequencies	Filter	Slope	Frequency(Hz)
Recommended	High Pass	12db/octButwrth	35
	Low Pass	24db/octButwrth	80-120
Limiter	Voltage		
RMS	89		
PEAK 3dB above	126		



S11BP

Crossover Frequencies	Filter	Slope	Frequency(Hz)
Recommended	High Pass	12db/octButwrth	35
	Low Pass	24db/octButwrth	80-160
Limiter	Voltage		
RMS	40		
PEAK 3dB above	56		

12BP-IG

Crossover Frequencies	Filter	Slope	Frequency(Hz)
Recommended	High Pass	12db/octButwrth	28
	Low Pass	24db/octButwrth	80-120
Limiter	Voltage		
RMS	89		
PEAK 3dB above	126		

S28BP

Crossover Frequencies	Filter	Slope	Frequency(Hz)
Recommended	High Pass	24db/octButwrth	35
	Low Pass	24db/octButwrth	100-160
Equalization	Frequencies (Hz)	BW / Q	Gain(db)
	48	.48 / 3	3
	85	.5 / 2.8	4
Limiter	Voltage		
RMS	40		
PEAK 3dB above	56		